



EV12-100(12V100Ah)



Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	100Ah@20hr-rate to 1.75V per cell @25°C
Weight	Approx. 31.5 Kg (Tolerance ±2%)
Internal Resistance	Approx. 5.0 mΩ
Terminal	F12(M8)
Max. Discharge Current	1000A (5 sec)
Cold Cranking Ampere(CCA)	630A
Maximum Charging Current	30.0 A
Reference Capacity	C3 78.3AH
	C5 85.0AH
	C10 95.0AH
	C20 100.0AH
Float Charging Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C
	Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charged batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



EV (Electric Vehicle) series is specially designed for frequent discharge deep cycle application. By using the specially designed active material, strong grids and thick plate construction, the EV series battery offers reliable performance in high load situations and could provide competitive cycle performance. Suitable for Electric Vehicle and Golf cart; Industrial equipment, Floor machines, Forklifts, Aerial lifts, and Robotics; Marine, RV, and no-idle solutions; Mobility and Medical equipment; and most outdoor application.



ISO 9001



ISO 14001



OHSAS 18001




MH 28539



G4M20206-0910-E-16

Dimensions



Constant Current Discharge Characteristics : A(25°C)

F.V/Time	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	107.0	61.8	36.6	27.8	21.9	18.5	12.3	10.2	5.20
1.65V	104.8	60.7	36.0	27.4	21.6	18.3	12.2	10.1	5.15
1.70V	101.8	59.1	35.1	26.9	21.2	18.0	12.0	10.0	5.09
1.75V	97.8	57.0	34.0	26.1	20.7	17.6	11.7	9.77	5.00
1.80V	92.2	54.1	32.5	25.0	19.9	17.0	11.4	9.50	4.88
1.85V	84.4	50.0	30.2	23.5	18.8	16.1	10.8	9.12	4.70









Constant Power Discharge Characteristics : WPC(25°C)

F.V/Time	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	194	116	69.4	53.2	42.1	35.7	24.0	20.0	10.2
1.65V	193	115	68.7	52.7	41.7	35.5	23.8	19.9	10.2
1.70V	189	112	67.3	51.7	41.0	35.0	23.5	19.6	10.0
1.75V	183	109	65.4	50.5	40.1	34.3	23.0	19.3	9.88
1.80V	174	104	62.7	48.6	38.8	33.2	22.4	18.8	9.65
1.85V	161	96	58.7	45.8	36.7	31.7	21.4	18.0	9.31

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.



EV12-100(12V100Ah)



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.

For Battery Sales + EPA Battery Recycling and AC / DC Power Services, please contact:
Moore & Moore Solutions, Inc.
 Phone: 484-302-7009
 Email: mr@mooreu.com
www.MooreU.com