



RA12-75A(12V75Ah)

Specification



RA series is a general purpose battery with 12 years design life in float service. It meets with IEC, JIS, BS and YDT standards. With advanced AGM valve regulated technology and high purity raw material, the RA series battery maintains high consistency for better performance and reliable standby service life. It is suitable for UPS/EPS, Telecom, power grid, medical equipment, emergency light and security system applications.



ISO 9001



ISO 14001



OHSAS 18001







MH 28539



G4M20206-0910-E-16

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity	75Ah@10hour-rate to 1.80V per cell @25°C
Weight	Approx. 23.0 Kg (Tolerance ±2.0%)
Internal Resistance	Approx. 5.8 mΩ
Terminal	F15(M6)/F11(M6)
Max. Discharge Current	750A (5 sec)
Short Circuit Current	1720A
Design Life	12 years (Float charging)
Recommended Maximum Charging Current	22.5 A
Reference Capacity	C3 58.2AH C5 67.0AH C10 75.0AH C20 79.4AH
Standby Use Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.

Dimensions



F11 TERMINAL

Length	260±2mm (10.2 inches)
Width	169±2mm (6.65 inches)
Height	211±2mm (8.31 inches)
Total Height	216±2mm (8.50 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	180.6	136.0	78.7	46.6	27.9	20.5	16.7	14.1	9.40	7.99	4.10
1.65V	175.2	132.4	77.0	45.8	27.5	20.2	16.5	13.9	9.31	7.92	4.07
1.70V	168.1	127.7	74.7	44.6	27.0	19.9	16.2	13.7	9.18	7.82	4.02
1.75V	159.0	121.6	71.7	43.1	26.3	19.4	15.8	13.4	9.01	7.68	3.97
1.80V	147.3	113.8	67.8	41.2	25.3	18.8	15.3	13.0	8.79	7.50	3.89
1.85V	132.7	103.9	62.9	38.6	24.1	17.9	14.7	12.5	8.49	7.27	3.78

Constant Power Discharge Characteristics : WPC (25°C)


F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	311.5	241.3	145.1	88.5	53.8	39.8	32.5	27.5	18.6	16.0	8.19
1.65V	310.2	239.9	144.0	87.8	53.4	39.5	32.2	27.3	18.5	15.8	8.14
1.70V	301.1	233.4	140.5	85.9	52.5	38.9	31.8	27.0	18.3	15.6	8.06
1.75V	289.8	225.5	136.3	83.4	51.3	38.1	31.2	26.5	18.0	15.4	7.96
1.80V	273.2	214.0	130.2	80.0	49.7	37.0	30.3	25.8	17.6	15.0	7.81
1.85V	250.6	198.1	121.9	75.6	47.5	35.5	29.2	24.9	17.0	14.6	7.61

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.


RA12-75A(12V75Ah)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use



Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



For Battery Sales + EPA Battery Recycling and AC / DC Power Services, please contact:

Moore & Moore Solutions, Inc.
 Phone: 484-302-7009
 Email: mr@mooreu.com
www.MooreU.com