



LHR Series-High Rate


LHR12550W(12V550W)

Specifications

Rated Voltage	12V		
Nominal Rate(W ₁₅ , 1.67V/cell)	550W/cell		
Nominal Capacity(C ₁₀ , 1.80V/cell)	140Ah		
Dimension	Length	483±2mm (19.0 inches)	
	Width	170±2mm (6.69 inches)	
	Container Height	238.5±2mm (9.39 inches)	
	Total Height	238.5±2mm (9.39 inches)	
Approx Weight	46.1kg (101.6 lbs)		
Terminal	M8		
Container Material	ABS: UL 94 HB or V-0 optional		
Rated Capacity(25°C)	140.0 Ah	C10(14.0A, 1.80V/cell)	
	130.4 Ah	C8(16.3A, 1.80V/cell)	
	123.0 Ah	C5(24.6A, 1.75V/cell)	
	109.2 Ah	C3(36.4A, 1.75V/cell)	
	89.1 Ah	C1(89.1A, 1.60V/cell)	
Max. Discharge Current	1400A (5s)		
Internal Resistance(25°C)	Approx 3.5mΩ		
Operating Temp. Range	Discharge	-20 ~ 55°C (-4 ~ 131°F)	
	Charge	-20 ~ 40°C (-4 ~ 104°F)	
	Storage	-15 ~ 50°C (5 ~ 122°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)		
Max.Charging Current(25°C)	35.0A		
Charge voltage(25°C)	Float	2.25 ~ 2.30V/cell	Temp. Coefficient -3mV/cell/°C
	Equalization	2.30~2.40V/cell	-4mV/cell/°C
Effect of temp. to Capacity	40°C (104°F)	106%	
	25°C (77°F)	100%	
	0°C (32°F)	86%	
Self Discharge	≤3%/month @ 25°C		



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	8h	10h
1.85V/cell	329.0	262.7	227.7	179.1	124.1	95.1	77.0	56.6	46.3	34.5	27.2	23.0	15.9	13.6
1.80V/cell	374.2	298.2	258.1	202.5	139.9	101.0	79.6	58.3	49.0	35.6	28.3	24.0	16.3	14.0
1.75V/cell	406.9	323.7	279.7	218.8	150.7	107.0	82.9	60.7	50.9	36.4	29.2	24.6	16.4	14.1
1.70V/cell	434.5	344.8	296.7	231.8	159.6	113.1	86.5	63.2	52.1	37.2	29.9	25.2	16.7	14.2
1.67V/cell	449.7	355.7	305.4	238.1	163.4	115.6	87.5	64.9	53.3	38.0	30.3	25.5	16.9	14.4
1.60V/cell	465.6	367.8	314.9	244.2	167.3	118.6	89.1	67.1	54.4	38.9	31.0	26.0	16.9	14.5

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	8h	10h
1.85V/cell	614.5	494.2	431.2	340.6	237.2	182.8	149.0	109.7	90.0	67.3	53.4	45.4	31.6	27.1
1.80V/cell	687.3	552.8	482.4	381.1	265.3	192.8	153.2	112.4	94.8	69.2	55.2	47.0	32.2	27.8
1.75V/cell	734.4	590.6	515.4	407.1	283.4	203.2	158.8	116.5	98.1	70.5	56.9	48.2	32.4	27.9
1.70V/cell	771.2	620.2	541.2	427.5	297.7	213.2	164.9	120.8	100.0	71.8	58.0	49.1	32.9	28.1
1.67V/cell	783.8	630.3	550.0	434.5	302.5	216.8	165.7	123.3	102.0	73.1	58.6	49.6	33.2	28.4
1.60V/cell	794.7	639.1	557.7	440.6	306.7	220.3	167.6	126.6	103.3	74.5	59.6	50.4	33.3	28.6



IEEE/UL Battery
Sizing by
MooreU
610-952-6067
www.mooreu.com




LHR Series-High Rate

LHR12550W(12V550W)

Applications

- UPS
- Hospitals & Testing Laboratories
- Emergency Power Supply
- Banks & Financial Markets
- Industrial Process Control Facilities
- Data & Network Operation Centers


General Features

- High quality AGM separator: extend cycle life and prevent micro short circuit
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- Unique vent valve design: reduce water losing and prevent air/spark going inside


Standards

- Compliance with IEC 60896 and YD/T 3427 standards
- Manufactured in Leoch@IATF16949, ISO 45001, ISO 9001 and ISO 14001 certified production facilities


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Temperature Effects on Long Term Float Life



Sales Offices Worldwide

IEEE/UL Battery
Sizing by
MooreU
610-952-6067
www.mooreu.com



China Sales Office
5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com

HongKong Sales Office
Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,
Tsuen Wan, New Territories, Hong Kong
Tel: +852 35786666
Fax: +44 1452 690125
E-mail: sales.hk@leoch.com

Singapore Sales Office
No. 1 Tech Park Crescent,
Singapore 638131
Tel: +65 68636078
Fax: +65 6863 6079
Email: sales.sg@Leoch.com

Australia Sales Office
2/29 Tarlington Place, Smithfield. NSW 2164
Australia
Tel: 02 9756 0950
E-mail: sales.au@leoch.com

North America Sales Office
19751 Descartes
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

UK Sales Office
9B Wheatstone Court, Waterwells, Business Park,
Gloucester, GL2-2AQ, UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 1452 690125
E-mail: Sales.Europe@leoch.com
Http://www.leoch.eu

EMEA Sales Office
1 Deligiorgi St., 121 31 Athens,
Greece
Tel: +30 210 5760318 (2 lines)
E-mail: support_EMEA@leoch.com
Http://www.leoch.eu

India Sales Office
Shed no. A-53(b), 2nd Stage of Peenya Industrial Area,
Bangalore North Taluk, Bangalore-560058, India
Tel: +91-80-23440018/23440019
Fax: +91-80-23440017
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)

© 1999-2022 LEOCH. All rights reserved.
Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.
Subject to revisions without prior notice.

Publication No.: LB-LHR12550W-PD-EN-V1.0-202201